



SINGLE LADDER



TECHNICAL SPECIFICATION

- Safety yellow fibreglass
- Super strong, durable box rails
- Weather resistant - No water absorption
- Low maintenance
- High electrical resistance
- Lightest weight for equivalent load rating
- Dramatic reduction in sway and twist
- Specially designed non-slip "D" profile rungs

POWERMASTER SINGLE LADDER (FND)

Model	Height	Load Rating	Code
FND 2.4	2.4 m	160Kg	HCP-FND24-ESPM-001
FND 3.0	3.0 m	160Kg	HCP-FND30-ESPM-002
FND 3.6	3.6 m	160Kg	HCP-FND36-ESPM-003
FND 4.2	4.2 m	160Kg	HCP-FND42-ESPM-004
FND 4.8	4.8 m	160Kg	HCP-FND48-ESPM-005
FND 5.4	5.4 m	160Kg	HCP-FND55-ESPM-006

TRADEMASTER SINGLE LADDER (FNR)

Model	Height	Load Rating	Code
FNR 2.4	2.4 m	140Kg	HCP-FNR24-ESTM-001
FNR 3.0	3.0 m	140Kg	HCP-FNR30-ESTM-002
FNR 3.6	3.6 m	140Kg	HCP-FNR36-ESTM-003
FNR 4.2	4.2 m	140Kg	HCP-FNR42-ESTM-004
FNR 4.8	4.8 m	140Kg	HCP-FNR48-ESTM-005

CORROSIONMASTER SINGLE LADDER (FNF)

Model	Height	Load Rating	Weight	Code
FNF 2.4	2.4 m	150 Kg	6.6 Kg	HCP-FNF24-ESC-001
FNF 3.0	3.0 m	150 Kg	8.1 Kg	HCP-FNF30-ESC-002
FNF 3.6	3.6 m	150 Kg	9.6 Kg	HCP-FNF36-ESC-003
FNF 4.2	4.2 m	150 Kg	12.8 Kg	HCP-FNF42-ESC-004
FNF 4.8	4.8 m	150 Kg	14.6 Kg	HCP-FNF48-ESC-005
FNF 5.4	5.4 m	150 Kg	16.4 Kg	HCP-FNF54-ESC-006
FNF 6.0	6.0 m	150 Kg	18.2 Kg	HCP-FNF60-ESC-007

A climbing solution designed specifically for corrosive environments.


APPLICATION






SINGLE LADDER ACCESORIES

PS Pole strap attached to the top of the fly section to allow the ladder to be placed securely against a pole. Made with a tough polyurethane rubber pad sown to heavy duty nylon web. The common alternative is a Pole chain.




Code: HCP-PSESEE-001

PC Pole chain attached to the top of the fly section to allow the ladder to be placed securely against a pole. The common alternative is a Pole strap.




Code: HCP-PCSEEE-002

TL The top lash or tie off rope is attached to the top of the fly section of the ladder and is used to lash (tie) the top of the ladder to a pole or tree to stabilise the top of the ladder.




Code: HCP-TLESEE-003

BL Bottom 8mm lashing rope is tied from the base of the ladder to the workpole to prevent the ladder from slipping.




Code: HCP-BLESEE-004

CL Conventional style latch is used on TradeMaster ladders and is an option on PowerMaster range in lieu of the "Branch" latch. Preferred by users more comfortable with the older style ladder latch.




Code: HCP-CLESEE-005

CP The Centre Pull Rope can replace the side pull rope if required. Sometimes preferred by operators who use the haul rope to position the ladder on a pole. If this option is chosen the conventional latch option must be fitted.




Code: HCP-CPSEEE-006

CT Rope cleat (used by ETSA Utilities) is used to store the top lash rope when it is not in use.




Code: HCP-CTESEE-007

MK Companies (or individuals) can have the company name stencilled in indelible ink on the side of the ladder. Allows for easy identification of the ladder and the company when the ladder is in use or in transit.




Code: HCP-MKESEE-008

FB Rubber Boot attached to the top of the fly section protects building surfaces from damage due to the ladder being placed against the building.




Code: HCP-FBESEE-009

LV Levelze Leveler is a permanently attached automatically operating leveling system for use on extension ladders.




Code: HCP-LVESEE-010

GB Grab bar attached between the ladder feet and used to grab the ladder off a truck and to stabilise or "Foot" the ladder when positioning it.




Code: HCP-GBESEE-011

TB The tie down bar attaches to the bottom of the fly section of the PowerMaster ladders to allow users to tie the fly and base section together for security in transport.




Code: HCP-TBESEE-012

CH Cable hooks used predominantly in the telecommunications industry to allow users to rest the top of the ladder against a cable and work "mid-strand".




Code: HCP-CHESEE-013

QC Quick connect couplings in pairs. Permanently attached to extension ladders and platforms to enable the connection of the Levelok levelling leg. The Leveler leg can be removed when not in use.




Code: HCP-QCESEE-014

BF Bottom 8mm lashing rope is tied from the base of the ladder to the workpole to prevent the ladder from slipping. The red flag gives a visual warning of the presence of the rope.



Code: HCP-BFESEE-015

FP Shown here in conjunction with cable hooks. Protects the ladder from wear when placed directly on the electrical or support wires of the rail system.




Code: HCP-FPESEE-016




SINGLE LADDER ACCESORIES

AR 11mm Ladder rope in lieu of standard polypropylene rope can be selected as an option on PowerMaster range .




Code: HCP-ARESEE-017

SF The swivel foot maximises grip and adjusts to minor slopes. Shown with the gravel/ice pick in the raised position. This can be rotated to below the foot on loose ground where it digs in giving extra purchase.




Code:HCP-SFESEE-018

FL Automatic locking mechanism for the fly section of the ladder. Prevents the ladder sections separating when carried by two users. Automatically releases when the haul rope is tensioned to raise the ladder.




Code: HCP-FLESEE-019

FR Fibreglass rung used in lieu of aluminium. For use in corrosion resistant ladders and for users who require the absence of metal in the work area.




Code: HCP-FRESEE-020

LW Rolling wheels attached to the top of the fly section on an extension ladder allows the fly section to easily extend by rolling up the wall. Used predominantly by the fire brigade.




Code:HCP-LWESEE-021

LL Levelok Leveler Leg for use on uneven ground. It is detachable from the ladder to minimise weight. Used in conjunction with "quick-connect" brackets which are attached to the ladder or platform.



Code: HCP-LLESEE-022

RF Rubber feet are an alternative to the swivel feet used on the PowerMaster range. Sometimes preferred in sandy or muddy conditions the sand/mud may clogg the swivel feet. The tough polyurethane foot is maintenance free.



Code: HCP-RFESEE-023